



Modular reception system

Twin DVB-S/S2 & DVB-T/T2/C - DVB-T transmodulators

Converting of 2 DVB-S/S2 & DVB-T/T2/C modulated input signals into 2 COFDM modulated DVB-T channels.

- common interface
- TS processing:
 - service multiplexing - any input to any output
 - PCR restamping
 - PSI/SI regeneration
 - NIT generation
 - PMT version monitoring
- Web control and SNMP monitoring
- loop through RF distributing at input and output
- DIN rail or wall mounting
- robust die-cast housing
- connectors:
 - RF input/output - type F
 - Ethernet control interface - RJ-45
 - 2xCI ports - PCMCIA (tdx420C, ttx420C)
 - screw terminal block for DC entry
 - power distribution bus

tdx420C
DVB-S/S2 - DVB-T transmodulator with two CAMs

ttx420C
DVB-T/T2/C - DVB-T transmodulator with two CAMs

tdx420
DVB-S/S2 - DVB-T transmodulator

ttx420
DVB-T/T2/C - DVB-T transmodulator



Technical specifications

T Y P E		tdx420C / tdx420		ttx420C / ttx420		
Ordering number		03855 / 03855F		03856 / 03856F		
Number of channels				2		
RF input	frequency range	950-2150 MHz		47-862 MHz		
	LNB powering/control	0/13/18 V & 22 kHz, 500 mA max. DISEqC 1.0, EN50607, EN50494		12 V 100 mA		
	level/impedance	45-85 dBμV / 75 Ω		40-80 dBμV / 75 Ω		
	loop through gain	-1 ± 1 dB		0 ± 1 dB		
	standard	DVB-S	DVB-S2**	DVB-T	DVB-T2	DVB-C
	modulation	QPSK	QPSK, 8PSK APSK 8/16/32	QPSK, QAM16, QAM64	QPSK, QAM16, QAM64, QAM256	QAM16, QAM32, QAM64, QAM128, QAM256
	bandwidth	-	-	7 MHz/8 MHz	7 MHz/8 MHz	-
	symbol rate	2 ÷ 45 Ms/s	2 ÷ 45 Ms/s	-	-	1 ÷ 7.2 Ms/s
	code rate	1/2, 2/3, 3/4, 5/6, 7/8	QPSK 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 8PSK 3/5, 2/3, 3/4, 5/6, 8/9, 9/10	1/2, 2/3, 3/4, 5/6, 7/8	1/2, 3/5, 2/3, 3/4 4/5, 5/6	-
roll of	35 %	20 %, 25 %, 35 %	-	-	15 %	
RF output	frequency range	100 - 858 MHz, by step 100 kHz				
	channel allocation	adjacent				
	level/impedance	90 ± 2 dBμV/75 Ω				
	spurious level	< -60 dB				
	MER	≥ 38 dB (100-780 MHz); ≥ 35 dB (780-860 MHz)				
	modulation DVB-T	QPSK, QAM16, QAM64				
	channel bandwidth	7/8 MHz				
	guard interval	1/4, 1/8, 1/16, 1/32				
	code rate	1/2, 2/3, 3/4, 5/6, 7/8				
	transmission mode	2K				
	total output level adjustment	0 ÷ -15.0 dB by 1 dB step				
loop through frequency range/loss	47-862 MHz / ≤ 2.5 dB					
Transport stream parameters	max. bit rate	output 31670 kbps				
max. PID filter count	unlimited					
Management port	standard IEE802.3 10/100 Base T					
Current consumption*	12 V 550 mA		12 V 650 mA			
Operating temperature range	0° ÷ +50° C					
Dimensions/Weight (packed)	48.5x198x112 mm/0.9 kg					

pr. software control

* without external DC feeding and CAM, with two CAM's ≈0.95 A (for ttx420C), ≈0.85 A (for tdx420C)

** supports physical layer scrambling (PLS) and multiple input streams (MIS)